

SUBMITTAL SHEET

PIC WELDING ADHESIVE

PIC Welding Adhesive is used as a component for bonding PIC sheeting, jackets, and fitting covers. PIC welding adhesive has been specifically formulated to permanently bond joints together. Currently available in white or clear.

PIC welding adhesive can be applied with our applicator gun or similar hand pump oiler. Thin adhesive when necessary with PIC welding thinner as needed to promote smooth pumping. Do not use as a filler in gaps or joints as excessive adhesive will soften PVC. Typical application temperature is between 40°F and 100°F. If installing in lower temperature allow longer set-up time.

Typical Properties:

	US Standard	Metric
Weight	7.69 lbs/Gal	921 grams/liter
VOC Content	White 5.84 lbs/Gal Clear 5.93 lbs/Gal	White - 699 grams/liter Clear - 710 grams/liter
Coverage (gallon)	500 lineal feet	152 lineal meters

CAUTION: Extremely flammable. Keep away from heat, sparks, and open flame. Avoid prolonged contact with skin, and breathing of vapor and spray mist. Do not take internally. Close container after each use. Keep out of reach of children. For industrial use only.

For additional information, refer to PIC Reduced VOC welding adhesive and welding adhesive thinner containers.

Current material safety data sheets are available 24/7 at www.pic-plastics.com

PIC Plastics, Inc.
2232 N. Garrison Ave.
Carthage, MO 64836
P: 417-359-9896
P: 800-654-0409
F: 417-359-9899
www.pic-plastics.com

